

## EUTRAC Surface

Product Code: USXX.XX.XXX.XX

### Product description:

The Eutrac Surface 230V track system can be surface mounted or suspended. It is a three-circuit track system made from extruded aluminium profile and two PVC support profiles, each with two embedded 2.5mm cross-section copper conductors. Driver options include Fixed Output, DALI and 0-10v dimming. It is supplied in 1, 2, 3 or 4 metre sections in colour finishes Black, White, Aluminium or any RAL specified, and can be easily cut to exact lengths on-site. Additional features include integration into selected linear systems.


**5 YEAR**  
GUARANTEE

Product options	For exact specifications create a Project Datasheet
Dimensions (mm):	36 (W) x 32 (H) x 1000, 2000, 3000 or 4000 (L)
Cut-out (mm):	(cut on-site)
Lifetime:	50,000 hrs
Mounting type:	Surface Mounted, Suspended
Finish:	Matt Black, Matt White, Anodised Aluminium, Grey
Emergency:	

Lighting options	For exact specifications create a Project Datasheet
Light source:	Choose any compatible 230V Spotlights
Driver:	Fixed Output, 0-10V, L&TE, DALI, DMX
Colour temperature:	
Beam angle:	
Diffuser:	
Operating voltage:	230V
IP Rating:	IP20
CRI:	
Delivered Lumens (lm):	
Power consumption (W):	Maximum Load 3600W
Efficiency (lm/W):	
Optional Extras:	Endfeed (R/L), Straight Coupler, End Cap, X-coupler and more...

Additional Info
Add notes...

### Cross-section



### Accessories

