




QUAD BASIC 73

LINEAR MODULES



KEY FEATURES

- Surface and Suspended mounting
- Standard modular lengths
- Direct lighting with Osram LED boards
- Compact Osram fixed output or DALI dimmable drivers
- Opal or Micro Prismatic Optic (MPO) diffusers
- IP20 as standard
- White, Black and Silver finishes



60 YEARS
IN LIGHT

FOR MORE INFORMATION OR TO TALK ABOUT A PROJECT:

CALL: +44 (0) 1235 55 37 69
EMAIL: sales@optelma.co.uk

ISSUE DATE: 01/01/18

HEAD OFFICE
The Science Park
Abingdon
Oxfordshire
OX14 3YT


SHOWROOM
23 Bowling Green Lane
Clerkenwell
London
EC1R 0BD

PARIS OFFICE
28 Rue Charles
Baudelaire
75012 Paris
France


SWISS OFFICE
St. Urbangasse 53
Postfach 1738
CH-4502 Solothurn
Switzerland

QUAD BASIC 73 SPECIFICATIONS


PRODUCT OPTIONS	
Dimensions (mm):	73 (W) x 80 (H) x Modular lengths (Below)
Cut-out (mm):	N/A
Lifetime:	50,000 hrs
Mounting type:	Surface, Suspended
Finish:	White, Black, Silver
Emergency:	N/A
Operating voltage:	230V
IP Rating:	IP20
Light source:	Osram LED
Driver:	Fixed Output, DALI Dimmable
Colour temperature:	3000K, 4000K
Beam Angle:	N/A
Diffuser:	Opal, MPO, Asymmetric
CRI:	> 80
Optional Extras:	<i>Connectors available to create longer lengths</i>



SURFACE CROSS-SECTION (MM)



POLAR CURVE 4000K OPAL



POLAR CURVE 4000K MPO

CHOOSE A MODULAR LENGTH

Length (mm)	Opal (lm/W)	MPO (lm/W)
1210	4400 lm / 38 W	3600 lm / 38 W
1810	6400 lm / 56 W	5200 lm / 56 W
2410	8600 lm / 76 W	7000 lm / 76 W

*Luminaire luminous flux with Opal diffuser at 4000K.



60 YEARS
IN LIGHT

**FOR MORE INFORMATION
OR TO TALK ABOUT A PROJECT:**

CALL: +44 (0) 1235 55 37 69
EMAIL: sales@optelma.co.uk
ISSUE DATE: 01/01/18

HEAD OFFICE
The Science Park
Abingdon
Oxfordshire
OX14 3YT

SHOWROOM
23 Bowling Green Lane
Clerkenwell
London
EC1R 0BD


PARIS OFFICE
28 Rue Charles
Baudelaire
75012 Paris
France

SWISS OFFICE
St. Urbangasse 53
Postfach 1738
CH-4502 Solothurn
Switzerland


QUAD BASIC 73 COMPONENTS



WHITE
Powder-coated Matt
White painted finish.




OPAL DIFFUSER
Opal polycarbonate
diffuser.



**WIRE
SUSPENSION**
Stainless steel cable,
Max height 2500mm.
Max spacing 1.5M.




BLACK
Powder-coated Matt
Black painted finish.



MPO DIFFUSER
Micro Prismatic
Optical diffuser.



SILVER
Powder-coated Matt
Silver painted finish.



END CAPS
Plastic end caps,
supplied as standard.



**FOR MORE INFORMATION
OR TO TALK ABOUT A PROJECT:**

CALL: +44 (0) 1235 55 37 69
EMAIL: sales@optelma.co.uk

ISSUE DATE: 01/01/18

HEAD OFFICE
The Science Park
Abingdon
Oxfordshire
OX14 3YT

SHOWROOM
23 Bowling Green Lane
Clerkenwell
London
EC1R 0BD

PARIS OFFICE
28 Rue Charles
Baudelaire
75012 Paris
France

SWISS OFFICE
St. Urbangasse 53
Postfach 1738
CH-4502 Solothurn
Switzerland

**60 YEARS
IN LIGHT**

QUAD BASIC 73 SPECIFICATION CODE

AAAA - BB/C/D/E - F/GGG - HHHH/I								
AAAA PRODUCT ID	BB MOUNTING	C FINISH	D DRIVER	E DIFFUSER	F DIRECT LED	GGG CRI/ COLOUR	HHH LENGTH (mm)	I EMERGENCY
QB73	SM SP	B W S	F D	O M A	M	830 840	1210 1810 2410	

MOUNTING **'SM'** Surface Mounted, **'SP'** Suspended Parallel
 FINISH **'B'** Black, **'W'** White, **'S'** Silver
 DRIVER **'F'** Fixed Output, **'D'** DALI
 DIFFUSER **'O'** Opal, **'M'** MPO, **'A'** Asymmetric
 DIRECT LED **'M'** Medium power Osram LED boards
 CRI / COLOUR **'830'** CRI 80+ Colour 3000K, **'840'** CRI 80+ Colour 4000K
 LENGTH Modular lengths in millimetres
 EMERGENCY N/A



**60 YEARS
IN LIGHT**

**FOR MORE INFORMATION
OR TO TALK ABOUT A PROJECT:**

CALL: +44 (0) 1235 55 37 69
EMAIL: sales@optelma.co.uk

ISSUE DATE: 01/01/18

HEAD OFFICE
The Science Park
Abingdon
Oxfordshire
OX14 3YT

SHOWROOM
23 Bowling Green Lane
Clerkenwell
London
EC1R 0BD

PARIS OFFICE
28 Rue Charles
Baudelaire
75012 Paris
France

SWISS OFFICE
St. Urbangasse 53
Postfach 1738
CH-4502 Solothurn
Switzerland