




QUAD 100 FLAT

MODULAR, CONTINUOUS & MADE-TO-MEASURE



KEY FEATURES

- Suspended or Wall mounted indirect linear lights
- Standard modular lengths, continuous connected modules or made-to-measure project-specific lengths
- Indirect lighting with PHILIPS Fortimo LED boards and compact PHILIPS Xitanium Fixed Output drivers
- DALI dimmable option, or Casambi bluetooth control
- Integrated 3-hour emergency conversions available
- Matt White, Matt Black and Anodised Aluminium standard finishes, with many more on request including RAL & vinyl
- UGR compliant with up to 136 LL/CW



PHILIPS CASAMBI

**60 YEARS
IN LIGHT**

CALL: +44 (0) 1235 55 37 69

EMAIL: sales@optelma.co.uk

ISSUE DATE: 21/01/20

HEAD OFFICE

The Science Park
Abingdon
Oxfordshire OX14 3YT
United Kingdom

SHOWROOM

23 Bowling Green Lane
Clerkenwell
London EC1R 0BD
United Kingdom

FRANCE


28 Rue Charles
Baudelaire
75012 Paris
France

SWITZERLAND


St. Urbangasse 53
Postfach 1738
CH-4502 Solothurn
Switzerland

QUAD 100 FLAT SPECIFICATIONS


| PRODUCT OPTIONS | | | |
|---|--|------------------------------|-------------|
| Dimensions (mm): | 99 (W) x 50 (H) | | |
| Cut-out (mm): | N/A | | |
| Weight (kg): | 2.8 kg per Metre | | |
| Lifetime: | 50,000 hrs | | |
| Mounting type: | Suspended, Wall Mounted | | |
| Finish: | White (RAL9016), White (RAL9010), Black, Anodised Aluminium | | |
| Emergency: | DALI or Standard 3 hour emergency conversion (30% driver output) | | |
| Operating voltage: | 230V | | |
| IP Rating: | IP20 | | |
| Light source: | Philips High Efficiency LED [HE] | Philips High Output LED [HO] | |
| Source Lumens/M: | 2275 [4000K] | 3850 [4000K] | |
| Delivered Lumens/M: | 1690 [CLEAR] 1446 [OPAL] | 2861 [CLEAR] | 2447 [OPAL] |
| Power Watts/M: | 12.6 | 21.0 | |
| Driver: | Fixed Output, DALI Dimmable, Casambi control | | |
| Colour temperature: | 3000K, 4000K | | |
| Diffuser: | OPAL (LOR 63.55%), CLEAR (LOR 74.3%) | | |
| CRI: | 80+ | | |
| Optional Extras: (On request, Lead times will be affected) | Integrated Downlights, CRI90+, Tuneable White, RGB, RGBW, 2700K, 3500K, 5000K, 6000K LED, PIR/Daylight sensors, IP rated up to IP65, alternative finishes. | | |



INDIRECT CROSS-SECTION (MM)



DIRECT WALL CROSS-SECTION (MM)



POLAR CURVE 4000K OPAL (DIRECT)

MODULAR LENGTHS WITH FAST-TRACK LEAD TIMES

| Module Lengths | CLEAR [HO] Indirect only* | OPAL [HO] Indirect only* |
|----------------|---------------------------|--------------------------|
| 870 | 2452lm/18W | 2100lm/18W |
| 1150 | 3270lm/24W | 2796lm/24W |
| 1430 | 4088lm/30W | 3492lm/30W |
| 1710 | 4906lm/36W | 4188lm/36W |
| 1990 | 5724lm/42W | 4884lm/42W |
| 2270 | 6542lm/48W | 5580lm/48W |
| 2550 | 7360lm/54W | 6276lm/54W |
| 2830 | 8179lm/60W | 6972lm/60W |

CONNECTED CONTINUOUS MODULAR SYSTEM

| Start/End Modules | CLEAR [HO] Indirect** | OPAL [HO] Indirect** |
|-------------------|-----------------------|----------------------|
| 1150 | 3270lm/24W | 2796lm/24W |
| 1410 | 4088lm/30W | 3492lm/30W |
| 1710 | 4906lm/36W | 4188lm/36W |
| 1990 | 5724lm/42W | 4884lm/42W |
| 2830 | 8179lm/60W | 6972lm/60W |
| 90° Corner | | |
| 590x590 | 3270lm/24W | 2796lm/24W |
| Middle Modules | | |
| 2805 | 8179lm/60W | 6972lm/60W |
| 2805 Em. | 100lm [Em.] | 168lm [Em.] |

* Delivered lumen outputs with Philips Fortimo High Output 4000K LED. Modular lead times from 2 weeks. Custom options affect price & lead time.

** For connected continuous system 3-hour DALI Emergency is available in middle modules only. Start module includes 1 end cap & 1 straight connector, End module includes 1 end cap, Middle module includes 1 straight connector. Be sure to specify START/MIDDLE/END/LEFT/RIGHT.



60 YEARS
IN LIGHT

CALL: +44 (0) 1235 55 37 69

EMAIL: sales@optelma.co.uk

ISSUE DATE: 21/01/20

HEAD OFFICE

The Science Park
Abingdon
Oxfordshire OX14 3YT
United Kingdom

SHOWROOM

23 Bowling Green Lane
Clerkenwell
London EC1R 0BD
United Kingdom

FRANCE

28 Rue Charles
Baudelaire
75012 Paris
France


SWITZERLAND

St. Urbangasse 53
Postfach 1738
CH-4502 Solothurn
Switzerland

CUSTOM LIGHT SOURCES FOR MADE-TO-MEASURE SOLUTIONS


| Light Source | LED Source Output | Additional Information |
|---------------------------|----------------------------|-----------------------------|
| Opteline Board 24V LED | 1582lm/M / 15.2W/M | 50mm cut-points |
| Helvar Tuneable White LED | 4165lm/M / 21.7W/M | 2700K to 6500K |
| LEE Tuneable White LED | 1887lm/M / 10.5W/M | 2700K to 5700K |
| RGB 24V LED Tape | 470lm/M / 15W/M | 62.5mm cut-points |
| RGBW 24V LED Tape | 750lm/M / 30.8W/M | 62.5mm cut-points |
| Mini Fixed Downlight Ø52 | 105lm / 4.5W | 20°, 38°, 60° beam angles |
| Integrated 230V Track | See spotlight range online | 1-circuit or 3-circuit DALI |

* Source lumens output at 4000K. Custom options affect price & lead time. We have 60+ years experience in bespoke/made-to-measure lighting, so if what you want is not listed, please enquire.



POLAR CURVE 4000K CLEAR (DIRECT)


QUAD 100 FLAT COMPONENTS



MECHANICAL COUPLER
Flush connections between modules.




CORNICE SUPPORT
Fixing bracket for wall mounting the profile.



MITRED T-JUNCTION
Join more than one linear lighting section.



CHANGE-OF-PLANE
Continuous lighting from ceiling to wall.



MITRED CORNER
Let continuous light turn corners between 81° and 180°.



INTEGRATED DOWNLIGHTS
Fixed miniature downlights.



INTEGRATED 230V TRACK
Flush-fitting 230V track for integrated spotlights and more.



RGB LIGHTING
24V RGB LED lighting options available.



PIR SENSOR
Miniature Passive Infrared sensor for motion detection.

INTEGRATED EMERGENCY CONVERSIONS



The integrated Emergency conversion (Standard/DALI) will run the driver at 30% output for 3-hours. The converted drivers output is shared equally across each connected board, illuminating the entire length in emergency mode. This improves uniformity to comply with emergency regulations.

A maximum of 10 boards (2810mm module) can be connected to one emergency conversion kit. Longer lengths will require multiple emergency conversions.

| Module lengths | Medium Power Emergency* | High Power Emergency* |
|----------------|-------------------------|-----------------------|
| 850mm | 99.45lm | 168.3lm |
| 1130mm | 99.45lm | 168.3lm |
| 1410mm | 99.45lm | 168.3lm |
| 1690mm | 99.45lm | 168.3lm |
| 1970mm | 99.45lm | 168.3lm |
| 2250mm | 99.45lm | 168.3lm |
| 2530mm | 99.45lm | 168.3lm |
| 2810mm | 99.45lm | 168.3lm |



60 YEARS IN LIGHT

CALL: +44 (0) 1235 55 37 69
EMAIL: sales@optelma.co.uk

ISSUE DATE: 21/01/20

HEAD OFFICE
The Science Park
Abingdon
Oxfordshire OX14 3YT
United Kingdom

SHOWROOM
23 Bowling Green Lane
Clerkenwell
London EC1R 0BD
United Kingdom

FRANCE
28 Rue Charles
Baudelaire
75012 Paris
France

SWITZERLAND
St. Urbangasse 53
Postfach 1738
CH-4502 Solothurn
Switzerland

QUAD 100 FLAT SPECIFICATION CODE

| AAAA - BB/C/D/E - F/GGG - HHHH/I | | | | | | | | |
|----------------------------------|----------------|-------------------------|-------------|---------------|-----------------|---------------------------------------|--|----------------|
| AAAA PRODUCT ID | BB MOUNTING | C FINISH | D DRIVER | E DIFFUSER | F DIRECT LED | GGG CRI/ COLOUR | HHH LENGTH (mm) | I EMERGENCY |
| QF10 | SP WM | B W WW A X* | F D C | O C | E O X* | 827 830 840 8TW 8RW X* | 0870 1150 1430 1710 1990 2270 2550 2830 X* | E DE |

- MOUNTING **SP** Suspended Parallel, **WM** Wall Mounted
- FINISH **B** Matt Black, **W** White RAL 9016, **WW** White RAL 9010, **A** Anodised Aluminium, **X** Custom Finish
- DRIVER **F** Fixed Output, **D** DALI, **C** Casambi control
- DIFFUSER **O** Opal, **C** Clear
- DIRECT LED **E** High Efficiency 650lm boards, **O** High Output 1100lm boards, **X** Custom - specify details alongside code
- CRI / COLOUR **827** CRI 80+ Colour 2700K, **830** CRI 80+ Colour 3000K, **840** CRI 80+ Colour 4000K,
8TW CRI 80+ Tuneable White 2700K-6500K, **8RW** CRI 80+ RGBW LED, **X** Custom - specify details alongside code
- LENGTH Modular lengths in millimetres, **X** Specify custom length
- EMERGENCY **E** Standard Integrated Emergency, **DE** DALI Integrated Emergency

For through-wired continuous modules, specify: **'START'**, **'MIDDLE'**, **'END'**, **'LEFT'** or **'RIGHT'** to build light systems

STANDARD

Standard fixed option products for quick and easy specification. Point source LED and Linear LED solutions, organised into Track & Spots, Downlights, Recessed, Surface, Suspended and Wall mounted solutions.

MADE-TO-MEASURE

Versatile systems and luminaires with custom specifications for project-specific lighting. Available in custom sizes and lengths, with many options including curves, corners, finishes, integrated accessories and more.

BESPOKE

Bespoke luminaires demonstrating completely custom project solutions, designed with the clients from concept to delivery. Learn about the design process and inspire your next bespoke lighting project.



60 YEARS IN LIGHT

CALL: +44 (0) 1235 55 37 69
EMAIL: sales@optelma.co.uk
ISSUE DATE: 21/01/20

HEAD OFFICE

The Science Park
Abingdon
Oxfordshire OX14 3YT
United Kingdom

SHOWROOM

23 Bowling Green Lane
Clerkenwell
London EC1R 0BD
United Kingdom

FRANCE

28 Rue Charles
Baudelaire
75012 Paris
France

SWITZERLAND

St. Urbangasse 53
Postfach 1738
CH-4502 Solothurn
Switzerland