




# QUAD CURVE 60

## LINEAR SYSTEM



### KEY FEATURES

- Recessed, Surface Mounted and Suspended linear system
- Standard modular lengths, curves, junctions and corners to create organic lines and shapes of light
- Low, Medium or High Power Direct or Direct-Indirect LED
- Compact fixed output drivers, or a range of dimming options including DALI, 1-10V, Touch-Dim or Casambi control
- Integrated emergency conversions available on request
- White, Black, Silver, Graphite, Copper and Champagne finish



**CASAMBI**

**60 YEARS  
IN LIGHT**

#### FOR MORE INFORMATION OR TO TALK ABOUT A PROJECT:

CALL: +44 (0) 1235 55 37 69  
EMAIL: [sales@optelma.co.uk](mailto:sales@optelma.co.uk)

ISSUE DATE: 11/09/20

**HEAD OFFICE**  
The Science Park  
Abingdon  
Oxfordshire  
OX14 3YT


**SHOWROOM**  
23 Bowling Green Lane  
Clerkenwell  
London  
EC1R 0BD

**PARIS OFFICE**  
28 Rue Charles  
Baudelaire  
75012 Paris  
France


**SWISS OFFICE**  
St. Urbangasse 53  
Postfach 1738  
CH-4502 Solothurn  
Switzerland

## QUAD CURVE 60 SPECIFICATIONS

PRODUCT OPTIONS	
Dimensions (mm):	Direct Only: 60 (W) x 80 (H), Direct-Indirect: 60 (W) x 100 (H)
Cut-out (mm):	Direct Only: 60 (W) x 120 (H) including recessing bracket
Lifetime:	50,000 hrs
Mounting type:	Recessed, Surface, Suspended
Finish:	White, Black, Silver, Champagne Gold, Copper, Graphite
Emergency:	Standard emergency conversion on request
Operating voltage:	230V
IP Rating:	IP20
Light source:	Low Power, Medium Power, High Power
Driver:	Fixed Output, 1-10V, DALI, Touch Dim, Casambi control
Colour temperature:	2200K, 2700K, 3000K, 3500K, 4000K, 6500K
Beam Angle:	(Direct only 100% or Direct-Indirect 40/60%)
Diffuser:	Opal, MPO
CRI:	CRI80, CRI90
Optional Extras:	Additional finishes and shapes available on request



CROSS-SECTION RECESSED DIRECT (MM)



CROSS-SECTION SURFACE DIRECT (MM)

### CHOOSE A PROJECT-SPECIFIC LENGTH, CURVE OR CORNER MODULE.

Direct Modules (Recessed, Surface or Suspended)	Low Power Direct only*	Medium Power Direct only*	High Power Direct only*
Linear 600mm	1190lm/17W per metre	1730lm/23W per metre	2250lm/32W per metre
Linear 888mm			
Linear 1178mm			
Linear 1472mm			
Linear 2340mm			
90° Corner 500x500mm			
135° Bend* 480x480mm			
90° Bend* 480x480mm			
60° Bend* 480x480mm			
45° Bend* 1023x1023mm			
1/2 Curve 500-4000mm Rad.			
1/4 Curve 500-4000mm Rad.			
1/8 Curve 500-4000mm Rad.			
1/16 Curve 500-4000mm Rad.			

\*Luminaire luminous flux with Opal diffuser at 4000K. Corner is mitred, Bend is rounded angle, not available in Recessed version. Curve Radii Available: 500mm, 750mm, 1000mm, 1250mm, 1500mm, 1750mm, 2000mm, 2500mm, 3000mm, 3500mm, 4000mm



**60 YEARS**  
**IN LIGHT**

#### FOR MORE INFORMATION OR TO TALK ABOUT A PROJECT:

CALL: +44 (0) 1235 55 37 69  
EMAIL: [sales@optelma.co.uk](mailto:sales@optelma.co.uk)

ISSUE DATE: 11/09/20

**HEAD OFFICE**  
The Science Park  
Abingdon  
Oxfordshire  
OX14 3YT


**SHOWROOM**  
23 Bowling Green Lane  
Clerkenwell  
London  
EC1R 0BD

**PARIS OFFICE**  
28 Rue Charles  
Baudelaire  
75012 Paris  
France

**SWISS OFFICE**  
St. Urbangasse 53  
Postfach 1738  
CH-4502 Solothurn  
Switzerland

Direct-Indirect Modules (Suspended)	Low Power Direct-Indirect*	Medium Power Direct-Indirect*	High Power Direct-Indirect*
Linear 600mm	2820lm/27W per metre	4130lm/40W per metre	4970lm/52W per metre
Linear 888mm			
Linear 1178mm			
Linear 1472mm			
Linear 2340mm			
90° Corner 500x500mm			
135° Bend* 480x480mm			
90° Bend* 480x480mm			
60° Bend* 480x480mm			
45° Bend* 1023x1023mm			
1/2 Curve 500-4000mm Rad.			
1/4 Curve 500-4000mm Rad.			
1/8 Curve 500-4000mm Rad.			
1/16 Curve 500-4000mm Rad.			

\*Luminaire luminous flux with Opal diffuser at 4000K. Corner is mitred, Bend is rounded angle.  
Curve Radii Available: 500mm, 750mm, 1000mm, 1250mm, 1500mm, 1750mm, 2000mm, 2500mm, 3000mm, 3500mm, 4000mm




CURVE MODULES IN MULTIPLE RADII




Y-JUNCTIONS, X-JUNCTIONS AND MORE

## QUAD CURVE 60 COMPONENTS




**MATT WHITE**  
Powder-coated Matt  
White painted finish.

**GRAPHITE**  
Powder-coated  
graphite finish.



**MATT BLACK**  
Powder-coated Matt  
Black painted finish.

**CHAMPAGNE**  
Powder-coated  
champagne finish.



**MATT SILVER**  
Powder-coated Matt  
Silver painted finish.

**COPPER**  
Powder-coated  
copper finish.



**90° CORNER**  
Opal / MPO mitred  
corner modules with  
500mm linear sides.



**60° BEND**  
Opal / MPO rounded  
corner modules with  
480mm linear sides.



**90° BEND**  
Opal / MPO rounded  
corner modules with  
480mm linear sides.

**45° BEND**  
Opal / MPO rounded  
corner modules with  
1023mm linear sides.



**135° BEND**  
Opal / MPO rounded  
corner modules with  
480mm linear sides.



**JUNCTIONS/  
SHAPES**  
Crosses, Y-junctions  
and wave modules  
(except for recessed).



**60 YEARS  
IN LIGHT**

### FOR MORE INFORMATION OR TO TALK ABOUT A PROJECT:

CALL: +44 (0) 1235 55 37 69  
EMAIL: [sales@optelma.co.uk](mailto:sales@optelma.co.uk)

ISSUE DATE: 11/09/20

**HEAD OFFICE**  
The Science Park  
Abingdon  
Oxfordshire  
OX14 3YT

**SHOWROOM**  
23 Bowling Green Lane  
Clerkenwell  
London  
EC1R 0BD

**PARIS OFFICE**  
28 Rue Charles  
Baudelaire  
75012 Paris  
France

**SWISS OFFICE**  
St. Urbangasse 53  
Postfach 1738  
CH-4502 Solothurn  
Switzerland

## QUAD CURVE 60 SPECIFICATION CODE

AAAA - BB/C/D/E - F/GGG - HHHH/I										
AAAA PRODUCT ID	BB MOUNTING	C FINISH	D DRIVER	E DIFFUSER	F DIRECT LED	GGG CRI/ COLOUR	F INDIRECT LED	GGG CRI/ COLOUR	HHH LENGTH (mm)	I EMERGENCY
QU60 QC60	RE SM SP	B W S G C X*	F D 1 T C	O M	L M H	827 830 840 927 930 940	L M H	827 830 840 927 930 940	XXXX* LENGTH/ RADIUS IN MM	E

PRODUCT ID 'QU60' Linear 60mm modules, 'QC60' Curved 60mm modules (define radius)

MOUNTING 'RE' Recessed, 'SM' Surface Mounted, 'SP' Suspended Parallel

FINISH 'B' Black, 'W' White, 'S' Silver, 'G' Champagne Gold, 'C' Copper

DRIVER 'F' Fixed Output, 'D' DALI, '1' 1-10V, 'T' Touch Dim, 'C' Casambi control

DIFFUSER 'O' Opal, 'M' MPO, 'W' Asymmetric Wallwasher, 'S' Satin Louver

DIRECT LED 'L' Low power, 'M' Medium power, 'H' High power

CRI / COLOUR '827' CRI 80+ Colour 2700K, '830' CRI 80+ Colour 3000K, '840' CRI 80+ Colour 4000K,

'927' CRI 90+ Colour 2700K, '930' CRI 90+ Colour 3000K, '940' CRI 90+ Colour 4000K

INDIRECT LED 'L' Low power, 'M' Medium power, 'H' High power (LEAVE SECTION BLANK IF DIRECT ONLY)

CRI / COLOUR '827' CRI 80+ Colour 2700K, '830' CRI 80+ Colour 3000K, '840' CRI 80+ Colour 4000K,

'927' CRI 90+ Colour 2700K, '930' CRI 90+ Colour 3000K, '940' CRI 90+ Colour 4000K

LENGTH Modular lengths in millimetres

EMERGENCY 'E' Integrated Emergency - specify details alongside code

ADDITIONAL (+) 'L' 90° Corner, 'Y1' Y1 junction, 'Y2' Y2 junction, 'Y3' Y3 junction, 'Y4' Y4 junction, 'Y5' Y5 junction, 'Y6' Y6 junction, 'X1' X1 junction, 'X2' X2 junction, 'B45' 45° Bend, 'B60' 60° Bend, 'B90' 90° Bend, 'B135' 135° Bend, '1/2C' 1/2 Circle, '1/4C' 1/4 Circle, '1/8C' 1/8 Circle, '1/16C' 1/16 Circle - Waves on request

### STANDARD

Standard fixed option products for quick and easy specification. Point source LED and Linear LED solutions, organised into Track & Spots, Downlights, Recessed, Surface, Suspended and Wall mounted solutions.

### MADE-TO-MEASURE

Versatile systems and luminaires with custom specifications for project-specific lighting. Available in custom sizes and lengths, with many options including curves, corners, finishes, integrated accessories and more.

### BESPOKE

Bespoke luminaires demonstrating completely custom project solutions, designed with the clients from concept to delivery. Learn about the design process and inspire your next bespoke lighting project.



**60 YEARS**  
IN LIGHT

#### FOR MORE INFORMATION OR TO TALK ABOUT A PROJECT:

CALL: +44 (0) 1235 55 37 69

EMAIL: [sales@optelma.co.uk](mailto:sales@optelma.co.uk)

ISSUE DATE: 11/09/20

**HEAD OFFICE**  
The Science Park  
Abingdon  
Oxfordshire  
OX14 3YT

**SHOWROOM**  
23 Bowling Green Lane  
Clerkenwell  
London  
EC1R 0BD

**PARIS OFFICE**  
28 Rue Charles  
Baudelaire  
75012 Paris  
France

**SWISS OFFICE**  
St. Urbangasse 53  
Postfach 1738  
CH-4502 Solothurn  
Switzerland